

## DECLARATION OF COMPLIANCE

### Washing, Tube, Pipe and Tank Brushes

Product Name	Product Code	Filament	Size	Colour	Heat Tolerance	DOC Material
Rubber Edged Waterfed Brush	B2333	Soft/Medium PBT Bristle	265 x 90mm	BL, GN, RD, WT, YL	Min -30°C Max 120°C	PP/PBT
Tube Brush Head,	B3470	Medium/Stiff PBT Bristle	70mm Ø	BL, GN, RD, WT, YL, BK	Min -30°C Max 120°C	PP/PBT
Tube Brush Head	B3480	Medium/Stiff PBT Bristle	80mm Ø	BL, GN, RD, WT, YL, BK	Min -30°C Max 120°C	PP/PBT
Tube Brush Head	B3490	Medium/Stiff PBT Bristle	90mm Ø	BL, GN, RD, WT, YL, BK	Min -30°C Max 120°C	PP/PBT
Tube Brush Head	B3405	Medium/Stiff PBT Bristle	105mm Ø	BL, GN, RD, WT, YL, BK	Min -30°C Max 120°C	PP/PBT
Tube Brush Head	B3420	Medium/Stiff PBT Bristle	120mm Ø	BL, GN, RD, WT, YL, BK, PU	Min -30°C Max 120°C	PP/PBT
High Reach Flexible Pipe Brush, 50mmØ	B3550	Medium/Stiff PBT Bristle	580 x 300mm	BL	Min -30°C Max 120°C	PP/PBT
High Reach Flexible Pipe Brush, 100mmØ	B3500	Soft/Medium PBT Bristle	600 x 340mm	BL, RD, GN, YL	Min -30°C Max 120°C	PP/PBT
Tank Brush	B2820	Soft/Medium PBT Bristle	200 x 120mm	BL, GN, RD, WT, YL	Min -30°C Max 120°C	PP/PBT
Tank Brush	B2920	Medium/Stiff PBT Bristle	200 x 120mm	BL, GN, RD, WT, YL, BK, BN, GT, OR, PU, PK	Min -30°C Max 120°C	PP/PBT
Wide-Angled Waterfed Brush	B0528	Medium/Stiff PBT Bristle	285 x 120mm	BL, GN, RD, WT, YL	Min -30°C Max 120°C	PP/PBT

**Brush block:** Polypropylene grade (98%) - master batch (2%); White, Blue, Red, Yellow, Green, Black, Orange, Purple, Brown, Grey and Pink.

**Filaments:** Polyester PBT (Polybutyleneterephthalate).

**Wire staple:** Stainless steel (AISI 304)

We confirm that the above-mentioned products fulfil the requirements on materials and articles used for food contact as described in the European Regulation 10/2011/EC as amended up to and including 202/2014/EC. The master batches are furthermore in compliance with European Resolution Res AP (89) 1.

Substances used for the manufacturing of the products are all listed in Annex I of Regulation 10/2011/EC as amended up to and including 202/2014/EC. The products contain substances restricted by specific migration limits as defined in Regulation 10/2011/EC Annex I. The products have been tested for overall and specific migration according to the specifications in Regulation 10/2011/EC as amended up to and including 202/2014/EC. Both overall and specific migration limits are complied with when the products are used as specified.

The products can be used for contact with all kinds of foodstuffs at maximum 40°C for a maximum of 1 hour.

The following substances also authorised as direct food additives (dual use additives) are present in the products:

- **Ref no. 24550, Stearic Acid**
- **Ref no. 56585, Glycerol, Esters with Stearic Acid**
- **Ref no. 92080, Talc**
- **Ref no. 93440, Titanium Dioxide**
- **Ref no. 46640, BHT**

Furthermore, the various colours of injection moulded plastic contain the following dual use additives:

- **White, Blue, Yellow, Green, Purple and Grey:** TiO<sub>2</sub> and Calcium Stearate
- **Red and Orange:** TiO<sub>2</sub>, CaCO<sub>3</sub> and Calcium Stearate
- **Brown:** Fe<sub>2</sub>O<sub>3</sub>, Iron Oxide and Calcium Stearate

The products do not contain a functional barrier as defined in Regulation 10/2011/EC as amended up to and including 202/2014/EC.

The items do not apply any danger to health or environment according to article 3 in Framework Regulation 1935/2004/EC.

The items are manufactured according to Regulation 2023/2006/EC on good manufacturing practice. The items comply with current EU-legislation on plastic materials and articles intended for food contact as described in EC Regulation 10/2011/EC as amended up to and including 202/2014/EC and the Danish executive order no. 822 of 26/06/2013.

**FDA (American Food and Drug Administration):** All raw materials are in compliance with FDA-CFR 21 / Food code 2009.

**EU Regulations:** Made in accordance with EU regulations; 10/2011/EC as amended up to and including 202/2014/EC, 1935/2004/EC, 2023/2006, 579/2011/EC. EU directive; 93/43/EEC.

**Glass/Fork:** Fulfil the rules to be marked with the glass/fork symbol.


**Before use:** It is recommended to clean, disinfect and/or sterilise the article before use.

**After use:** clean, disinfect (tolerates all approved disinfectants) and sterilise the article after use according to the appropriate to its intended use, using the correct chemical, concentration, time and temperature. Sterilise in an autoclave max temp. 120°C (max temp for cleaning the article 134°C).

***This certificate was prepared on behalf of Klipspringer Ltd and the information included is to the best of our knowledge correct at the time of writing. Klipspringer offers the information within this document as a guide only, they do not represent any guarantee of the prescribed products in the sense of the legal guarantee regulations. It is the responsibility of the end user to ensure the items purchased are suitable for the intended application.***

Supplier/Importer	Klipspringer Ltd
Address	Rynor House, Farthing Road, Ipswich, Suffolk, UK. IP1 5AP
Telephone	+44 (0) 1473 461 800
Email	sales@klipspringer.com
Website	www.klipspringer.com

**Declaration of compliance in line with Annex 4 10/2011/EC**

Sheena Britton Technical Compliance Manager Klipspringer 11-05-2021		Date of Issue	11-05-2021
		Authorised by	S. Britton
		Revision No.	004
		Revised by	S. Britton