

Product Specification: pH Electrode (S062)

P19 Semi solid spear tipped pH Electrode

Recommended application: Suitable for Bread, dough, dairy products, fats, creams, fish & meat products, soil etc.

PH Range	0-14
E O Point	-25mV to +25mV
Connector	BNC (others available upon request)
Temp Range °C	0-80°C
Combination	Yes
Response Time	<30 secs 95% FSD
Body Type	glass
Ref. Type	AgCl, liquid filled Single Junction
Application	Semi Solids, Fruit, cheese
Junction Type	Frit Ceramic
Storage Solution	PEB-216
Lower Shaft Length	40mm +/-2mm
Lower Shaft Diameter	6mm
Recommended Cleaning Solution	PEB215



This document was prepared on behalf of Klipspringer Ltd and the information included is to the best of our knowledge correct at the time of writing. Klipspringer offers the information within this document as a guide only, they do not represent any guarantee of the prescribed products in the sense of the legal guarantee regulations. It is the responsibility of the end user to ensure the items purchased are suitable for the intended application.

Supplier/Importer: Klipspringer Ltd
Address: Rynor House, Farthing Road, Ipswich, Suffolk, UK. IP1 5AP
Telephone: 0044 (0) 1473 461800
Email/Website: info@klipspringer.com / www.klipspringer.com

Sheena Britton
 Technical Compliance Manager
 Klipspringer Ltd



21-03-17

Date of issue	21-03-17	Revision No.	001	Revised by	SB
Authorised by	S. Britton	Document No.	S062	Page 1 of 1	