

USER MANUAL



WashGuard - Coverall

Chemical Resistant Coverall.

Product Information

Product: R450

Material: 100% Polyamide, Coating: Polyurethane

En standards: EN 14605:2005 + A1:2009 and EN 343: 2019

EN 343 – Protection against foul weather

EN343



- X: (Top) Resistance to water penetration class
- Y: (Center) Water vapour resistance class
- R: (Bottom) Readymade garment rain tower test, optional

Please note that there is a risk of heat stress, depending on the surrounding temperature and degree of physical activity of the user.

WARNING- Restricted wearing time according to the following table:

Temperature of working environment	25°C	20°C	15°C	10°C	5°C
Wearing time (min)	60	75	100	240	-

Before use of the garment please check for visible defects such as: Holes, cracks, damaged fastenings, discolouration, or crackled surface areas. To avoid or minimize the amount of perspiration, we recommend the use of functional underwear underneath the garment.

EN14605 – Protective clothing against liquid chemicals



This PPE provides protection for the wearer when working with chemical substances. The standard lists performance requirements for clothing with liquid-tight (Type 3) or spray tight (Type 4) connections, including items providing protection to parts of the body only - Type PB [3] and PB [4].

INSTRUCTIONS - To achieve the best possible protection, the following instructions must be followed precisely. For maximum protection please read the product information for this product as well as other personal protection equipment used with this garment carefully. This can include eg. jacket, trousers, boots, gloves and facial mask. User must be aware that any area of the body not covered by other PPE is not protected. Liquids may penetrate the garment if it is not covered by boots or gloves.

MECHANICAL PROPERTIES OF THE MATERIAL -

Resistance to wear	6/6
Blocking	5/6
Flex cracking resistance	6/6
Puncture resistance	3/6
Tensile strength	4/6
Seam strength	5/6

Class table for chemical penetration –

Class	1	2	3	4	5	6
Time/min	10	30	60	120	240	480

1. Acetone 1	9. Toluene <0,7MIN	17. Nitric acid 2
2. Acetonitrile 1	29 Xylen < 5 min	18. Acetic acid 6
3. Dichlormethane 1	Bases:	27 Sulphuric acid 30% 6
4. Diethylamine <0,5 MIN	10. Sodiumhydroxid 10% w/w 6	Oils:
5. Ethylacetate 1	11. Sodiumhydroxid 40% w/w 6	22. Machine-oil 6
6. Hexane 1	12. Ammoniak aq 25% 6	Other Products:
7. Methanol 1	13. Sulphuric acid 20% 6	23. Hydrogen Peroxid H2O2 50% 6
28 1-Butan 1	14. Sulphuric acid 40% 6	24. Sodiumhypochlorite 6
Aromatic Solvents:	15. Sulphuric acid 95% 1	25. Anionic detergents 6
8. Nitrobenzene <1,5 MIN	16. Hydrochloric (min.37%) 3	26. Kationic detergents

General use and maintenance

Selection of appropriate PPE workwear should be determined by specific criteria related to individual job requirements. The choice of protective workwear is a compromise between protection or safety factors, and other important criteria such as durability, comfort, appearance and cost. Purchasers must determine the relative importance of each of these criteria before the optimum combination of fabric/garment properties can be determined for a specific job.

Storage:

Do NOT store in places subject to direct strong sunlight, as product may deteriorate. If the garment becomes wet allow to dry at room temperature before storing. To achieve the best possible protection, the following instructions must be followed precisely. For maximum protection please read the product information for this product, as well as other personal protection equipment used with this garment carefully. This can include e.g. jacket, trousers, boots and gloves. Only wear garments of suitable size and always check garment for flaws, holes etc. before use.

Maintenance:

Durability of garments is dependent on use and wash methods. Fabric – when stored in proper conditions (10 – 25°) – durability will remain for a minimum of 3 years. If washing instructions are not followed, the garment properties can be changed or disappear. Damaged garments should not be repaired but replaced with new ones. The garment does not become obsolete but deteriorates after wear and tear. Dispose of this garment appropriately at the end of its life – textile materials may be re-cycled.



The test results for certified properties were made after 5 washing and drying cycles. No impairments of appearance and function were noted.

To keep product functions, the following is recommended:

- **Regular change of clothes can prevent dirt and filth from fixating to garment.**
- **Dirty garments shall not be stored, but washed immediately with fat-soluble detergents, and be rinsed properly.**
- **Garments shall not be soaked and shall be washed separately.**
- **Detergents for colored wash are recommended for home washing.**
- **Do not use detergents that contain organic soap or bleaching agent.**
- **Detergents with perborates will affect color and reduce reflective properties.**
- **Detergents with chlorine will affect and reduce ant flame properties and color.**
- **Avoid over drying. Exposure to excessive drying temperatures will result in higher than normal shrinkage.**
- **In storage, garments should be kept in a dry, dark and airy room.**

WARNING: Dirty clothing may lead to a reduction in protection and if at any time this garment is un-recoverably damaged, soiled or contaminated, it should be replaced immediately.

Size Table

A: Height 166-194 cm

	S	M	L	XL	XXL	XXXL
Chest	92-99 cm	100-107 cm	108-115 cm	116-123 cm	124-131 cm	132-139 cm
Waist	78-85 cm	86-93 cm	94-101 cm	102-109 cm	110-117 cm	118-125 cm